

Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 26-6562-8
 Version number:
 6.01

 Revision date:
 20/06/2017
 Supersedes date:
 02/06/2017

Transportation version number: 1.00 (29/09/2010)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF

Telephone: +44 (0)870 241 6696 E Mail: info@meguiars.co.uk Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms





Ingredients:

Ingredient CAS Nbr EC No. % by Wt

Solvent naphtha (petroleum), medium aliphatic 64742-88-7 265-191-7 < 10

HAZARD STATEMENTS:

H315 Causes skin irritation.

H373 May cause damage to organs through prolonged or repeated exposure: nervous system |

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P260A Do not breathe vapours.

Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

EUH208 Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one. May produce an allergic reaction.

4% of the mixture consists of components of unknown acute oral toxicity.

Contains 9% of components with unknown hazards to the aquatic environment.

Information required per Regulation (EU) No 528/2012 on Biocidal Products:

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

Notes on labelling

H304 is not required on the label due to the product's viscosity

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration	% by W	't	Classification
			No.			
Non-Hazardous Ingredients	Mixture			50 -		Substance not classified as hazardous
Solvent naphtha (petroleum), medium aliphatic	7	265-191-7		< 10		Asp. Tox. 1, H304; STOT RE 1, H372 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315
Distillates (petroleum), hydrotreated light	64742-47- 8	265-149-8		5 - 9		Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3, H336; EUH066
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3		3 - 7	7	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336
Organic Salt NJTSR# 04499600-6842	Trade Secret			1 - 5	,	Substance with a Community level exposure limit in the workplace
Kaolin, calcined	92704-41- 1	296-473-8		1 - 5		Substance not classified as hazardous
Siloxanes and silicones, di-Me	63148-62- 9			1 - 5	,	Substance not classified as hazardous
Siloxanes and silicones, Di-Me, [[[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxylterminated	71750-80-			0.5 1.5		Acute Tox. 4, H302
Polymer Wax NJTSR# 04499600-6843	Trade Secret			0.5 - 1.5		Substance not classified as hazardous
White mineral oil (petroleum)	8042-47-5	232-455-8		0.1 -	1	Asp. Tox. 1, H304
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-	55965-84-			<=		Acute Tox. 3, H331;
one and 2-methyl-2H-isothiazol-3-one	9			0.00113		Acute Tox. 3, H311; Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic
						Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Formaldehyde
Carbon monoxide.
Carbon dioxide.
Irritant vapours or gases.

Condition

During combustion. During combustion. During combustion. During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent

material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Naphtha (petroleum), 64742-48-9 Manufacturer TWA:100 ppm

hydrotreated heavy determined

Organic Salt NJTSR# 04499600- Trade Secret UK HSC TWA:2 mg/m3

6842

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

Appearance/Odour Sweet, pleasant odour; Creamy purple liquid

Odour threshold *No data available.*

pH 8 - 9 Boiling point/boiling range 100 °C

Melting pointNot applicable.Flammability (solid, gas)Not applicable.Explosive propertiesNot classifiedOxidising propertiesNot classified

Flash point > 93 °C (200 °F)

Autoignition temperatureNot applicable.Flammable Limits(LEL)Not applicable.Flammable Limits(UEL)Not applicable.Vapour pressureNo data available.

Relative density 0.945 - 0.965 [*Ref Std*:WATER=1]

Water solubility Moderate

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Evaporation rateNo data available.Vapour densityNo data available.Decomposition temperatureNo data available.Viscosity15,000 - 30,000 mPa-sDensity0.95 - 0.97 g/ml

9.2. Other information

Molecular weight No data available.

Percent volatile 83.8 % weight [Test Method: Estimated]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eve contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Solvent naphtha (petroleum), medium aliphatic	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
Solvent naphtha (petroleum), medium aliphatic	Dermal	Rabbit	LD50 > 3,000 mg/kg
Solvent naphtha (petroleum), medium aliphatic	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Siloxanes and silicones, Di-Me, [[[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxy]-terminated	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Rabbit	LD50 87 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	LD50 40 mg/kg

 \overline{ATE} = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value					
	-						
Solvent naphtha (petroleum), medium aliphatic	Rabbit	Irritant					
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant					
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant					
Siloxanes and silicones, di-Me	Rabbit	No significant irritation					
White mineral oil (petroleum)	Rabbit	No significant irritation					
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Rabbit	Corrosive					
one							

Serious Eye Damage/Irritation

Name		Value
Solvent naphtha (petroleum), medium aliphatic	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Rabbit	Corrosive
one		

Skin Sensitisation

Name Species Value

Page: 8 of 17

Solvent naphtha (petroleum), medium aliphatic	Guinea	Not classified
	pig	
Distillates (petroleum), hydrotreated light	Guinea	Not classified
	pig	
Naphtha (petroleum), hydrotreated heavy	Guinea	Not classified
	pig	
White mineral oil (petroleum)	Guinea	Not classified
	pig	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Human	Sensitising
one	and	
	animal	

Photosensitisation

Name	Species	Value
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Human	Not sensitising
one	and	
	animal	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Solvent naphtha (petroleum), medium aliphatic	In vivo	Not mutagenic
Solvent naphtha (petroleum), medium aliphatic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	In Vitro	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Solvent naphtha (petroleum), medium aliphatic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Solvent naphtha (petroleum), medium aliphatic	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Mouse	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Solvent naphtha (petroleum), medium aliphatic	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Solvent naphtha (petroleum), medium aliphatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Solvent naphtha (petroleum), medium aliphatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Solvent naphtha (petroleum), medium aliphatic	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Solvent naphtha (petroleum), medium aliphatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphtha (petroleum), hydrotreated heavy	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	

İ	Mixture of 5-chloro-2-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
	methyl-2H-isothiazol-3-			data are not sufficient for	health	available	
	one and 2-methyl-2H-			classification	hazards		
	isothiazol-3-one						

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Solvent naphtha (petroleum), medium aliphatic	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Solvent naphtha (petroleum), medium aliphatic	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Solvent naphtha (petroleum), medium aliphatic	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Solvent naphtha (petroleum), medium aliphatic	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Solvent naphtha (petroleum), medium aliphatic	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Solvent naphtha (petroleum), medium aliphatic	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Kaolin,	92704-41-1	1	Data not			
calcined			available or			
			insufficient for			
			classification			
Solvent	64742-88-7		Data not			
naphtha			available or			
(petroleum),			insufficient for			
medium			classification			
aliphatic						
Siloxanes and	63148-62-9		Data not			
silicones, di-			available or			
Me			insufficient for			
			classification			
Organic Salt	Trade Secret		Data not			
NJTSR#			available or			
04499600-6842			insufficient for			
			classification			
Kaolin, calcined	92704-41-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Polymer Wax	Trade Secret		Data not			
NJTSR#			available or			
04499600-6843			insufficient for			
			classification			
Siloxanes and	71750-80-6		Data not			
silicones, Di-			available or			
Me, [[[3-[(2-			insufficient for			
aminoethyl)ami			classification			
no]propyl]dime						
thoxysilyl]oxy]						
-terminated						
Naphtha	64742-48-9		Data not			
(petroleum),			available or			
hydrotreated			insufficient for			
heavy			classification			
Solvent	64742-88-7	Green Algae	Estimated	72 hours	No obs Effect	4 mg/l
naphtha					Level	
(petroleum),				1		
medium						
aliphatic	64545 00 =	TTT	T), , , , , , , , , , , , , , , , , , ,	0.40 "
Solvent	64742-88-7	Water flea	Estimated	21 days	No obs Effect	0.48 mg/l
naphtha					Level	
(petroleum),				1		
medium				1		
aliphatic	64742 00 7		D. C. A. S.	70.1	D.CC / T 1	0.2 //
Solvent	64742-88-7	Green Algae	Estimated	72 hours	Effect Level	8.3 mg/l
naphtha				1	50%	
(petroleum),				<u> </u>		

medium						
aliphatic						
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Rainbow trout	Estimated	96 hours	Lethal Level 50%	20 mg/l
Mixture of 5- chloro-2- methyl-2H- isothiazol-3- one and 2- methyl-2H- isothiazol-3- one	55965-84-9	Diatom	Experimental	72 hours	NOEC	0.01 mg/l
Mixture of 5- chloro-2- methyl-2H- isothiazol-3- one and 2- methyl-2H- isothiazol-3- one	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
Mixture of 5- chloro-2- methyl-2H- isothiazol-3- one and 2- methyl-2H- isothiazol-3- one	55965-84-9	Diatom	Experimental	72 hours	EC50	0.021 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Distillates (petroleum), hydrotreated	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l

light						
White mineral	8042-47-5	Green algae	Estimated	72 hours	No obs Effect	>100 mg/l
oil (petroleum)					Level	
White mineral	8042-47-5	Water flea	Estimated	48 hours	Effect Level	>100 mg/l
oil (petroleum)					50%	
White mineral	8042-47-5	Water flea	Estimated	21 days	No obs Effect	>100 mg/l
oil (petroleum)				-	Level	
White mineral	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level	>100 mg/l
oil (petroleum)					50%	

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, Di-Me, [[[3-[(2-aminoethyl)ami no]propyl]dime thoxysilyl]oxy]-terminated		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymer Wax NJTSR# 04499600-6843	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Organic Salt NJTSR# 04499600-6842	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

Solvent	64742-88-7	Experimental	28 days	CO2 evolution	55 % weight	OECD 301B - Modified
naphtha		Biodegradation				sturm or CO2
(petroleum),						
medium						
aliphatic						
Mixture of 5-	55965-84-9	Data not	N/A	N/A	N/A	N/A
chloro-2-		available or				
methyl-2H-		insufficient for				
isothiazol-3-		classification				
one and 2-						
methyl-2H-						
isothiazol-3-						
one						

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, Di-Me, [[[3-[(2-aminoethyl)ami no]propyl]dime thoxysilyl]oxy]-terminated		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymer Wax NJTSR# 04499600-6843	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Non-Hazardous Ingredients		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Organic Salt NJTSR#	Trade Secret	Data not available or	N/A	N/A	N/A	N/A

04499600-6842		insufficient for classification				
Naphtha (petroleum), hydrotreated heavy	64742-48-9		N/A	N/A	N/A	N/A
Mixture of 5- chloro-2- methyl-2H- isothiazol-3- one and 2- methyl-2H- isothiazol-3- one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

EUH066

SECTION 16: Other information

List of relevant H statements

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.

Revision information:

CLP: Ingredient table information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom MSDSs are available at www.meguiars.co.uk