

Mercedes-Benz

AP00.20-U-1208DB SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 211

except AMG models

Passenger cars Model Year 2006



Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading:				
Service work to be performed as advised by service advisor:		Confirm work below:	has been performed by signing	

i

US Service 1-11 and 15-20 apply to "Additional work" items only.

Vehicle determines need for US Service 12 (Engine oil and filter change) as well as US Service 13 or US Service 14.

Perform each service as described.

Completed	Σk		No	t OK	
-	\downarrow			↓	
US Service 1		Not applicable			
US Service 2 Required		every 52,000 mi or 4 years: Engine compartment			
		Replace engine air-cleaner insert	Engines 113,648,272		
US Service 3 Required		every 26,000 mi or 2 years: Engine compartment			
		Replace combination filter			AP83.00-P-8384T
US Service 4		Not applicable			
US Service 5 Required		every 65,000 mi or 5 years: Engine compartment			
		Replace fuel filter	Engines 113, 272		AP47.20-P-0780TC
US Service 5 Required		every 26,000 mi or 2 years: Engine compartment			
		Replace fuel filter	Engine 648		AP47.20-P-0780T
US Service 6		Not applicable			
US Service 7 Required		every 91,000 mi or 5 years: Engine compartment			
		Replace spark plugs	Engines 113		AP15.10-P-1580AB
US Service 7		every 78,000 mi or 5 years:			
Required		Engine compartment			
		Replace spark plugs	Engine 272		
US Service 8 Required		every 143,000 mi or 15 years: Engine compartment			
		Replace coolant	Gasoline engines		AP20.00-P-2080DA
			Diesel engine		AP20.00-P-2080BA
US Service 9		every 2 years:			
Required		Engine compartment			
		Replace brake fluid			AP42.00-P-4280R
		Check preload pressure of pressure reservoir			
US Service 9 Recommended		every 2 years:		_	
		Check body for paint damage by service advisor			AP98.00-P-9850BA
	_	Underside of vehicle		_	
		Chassis and load-bearing body components: Check for damage and corrosion by service advisor			AP00.20-P-0090BA
US Service 10 Recommended		every 5 years:			
		Tilt/sliding roof: Clean slide rails and slide shoes			AP77.20-P-7731A
US Service 11 Recommended		every 3 years: Interior			
		Panorama sliding roof: Clean and lubricate guide mechanism			AP77.20-P-7732PB
US Service 12 Required		every 13,000 mi or 1 year: Engine compartment			
		Engine oil and filter change	Engine 113		AP18.00-P-0101AF
			Engine 648		AP18.00-P-0101TC
			Engine 272		AP18.00-P-0101TS
L					

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
13	US Service	first at 26,000 mi or 2 years:	after first every 26,000 mi or 2 years	
	14		Not O	(
→			↓	
		Engine compartment - Required		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components in the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053BA
	_	Check condition of poly-V-belt	_	
	0	Engine 113, 648		
_	0	Engine 272	<u> </u>	
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851T
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Brake system		AP42.10-P-4210Z
	0	Power steering	Gasoline Engines	AP46.00-P-4611BB
			Diesel Engines	AP46.00-P-4611P
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210N
		Engine compartment - Recommended		
	0	Check auxiliary battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		AP54.10-U-5453A
		Interior - Required		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042TA
		Function test		
	0	Check Sensotronic Brake Control (SBC) hydraulic unit		AP42.50-P-4259A
	0	Check parking brake (function test only)		AP42.00-P-4290R
		Interior - Recommended		
		Function test		
	0	Warning/indicator lamps, illumination and interior lighting		
	0	Windshield washer system, incl. rear window washer (where applicable)		AP82.30-P-8252T
	0	Headlamp cleaning system		
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150M
		Wheels, brakes - Required		
	1 0	Check thickness of brake pads, front and rear		AP42.10-P-4253A

US Service	US Service		Not OK	
13	14		\downarrow	
1	<u> </u>			
	0	Correct tire inflation pressure and enter in		
		bar or psi. LF RF LR RR		
		bar/psi:		
		Wheels, brakes - Recommended		
'п	0	Inspect tires for damage and splits, measu-	П	AP40.10-P-4051Z
	O	re tread depth, enter in mm:		7 101.101 1.001.2
		LF RF LR RR		
		outside		
		inside		
_/		Underside of vehicle - Required		
		onacisiae or remaie mequinea		
† '	' † (Leakage - Major components	П	AP00.20-P-0053BA
	O	Check for chafe marks, line routing, dama-		7 00.20 . 003527.
		ged components		
		i In the event of leakage, determine cau-		
		se and perform repair via separate work or- der		
	0	Check front axle ball joints for play, check		AP33.20-P-3353BA
	O	rubber boots	_	AF33.20-F-3333BA
	0	Inspect condition of flexible discs		AP41.10-P-4152Z
	0	Inspect play of tie rod and drag link joints,		AP46.00-P-4653F
		inspect rubber boots		
		Trunk - Required		
	0	Correct inflation pressure of spare tire and		
		enter in bar or psi.		
		bar/psi:		
		Trunk - Recommended		
	0	Check main battery condition using "Mid-		AP54.10-U-5453A
		tronics MCR 717" Tester.		
		Attach Midtronics MCR 717 Test Report print out here.		
1	T	Vehicle front/rear - Recommended		
601		venicie iront/rear - neconimenaea		
	0	Check wiper blade condition		AP82.30-P-8253G
Co	ompleted 🗵		Not OK	
	↓		↓	
US Servi	ce 15 - 19	not applicable		
	rvice 20 uired	once at 39,000 mi: Underside of vehicle		
neq.	_			
	Ц	Automatic transmission - Oil and filter change		
		Transmission 722.6		AP27.00-P-2702I
		Transmission 722.9		AP27.00-P-2702W
		Transfer case - oil change (4MATIC models)		AP28.00-P-2801P
1	_	5 ·		